

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 March 2004 (11.03.2004)

PCT

(10) International Publication Number
WO 2004/020225 A1

(51) International Patent Classification⁷: B60B 33/00,
33/02

[GB/GB]; The Forge, 1 fauvel Place, Glossop, Derbyshire
SK16 7AR (GB).

(21) International Application Number:
PCT/GB2003/003700

(74) Agent: ALLMAN, Peter, John; Marks & Clerk, Sussex
House, 83-85 Mosley Street, Manchester M2 3LG (GB).

(22) International Filing Date: 26 August 2003 (26.08.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0219942.0 28 August 2002 (28.08.2002) GB
0303274.5 12 February 2003 (12.02.2003) GB

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): CAS-
TOR TECHNOLOGY LTD [GB/GB]; Monaghan House,
Claredon Street, Hyde, Cheshire, SK14 2EP (GB).


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): FOSTER, Alan

[Continued on next page]

(54) Title: IMPROVEMENTS IN OR RELATING TO CASTORS



(57) **Abstract:** A support structure for a castor, a castor provided with such a support- structure, and a castored trolley is described. The support structure comprises a first member 5, a second member 3 that is rotatable with respect to the first member about a pivot axis, and magnetic means 21, 23, 61, 63 that is operable up to a certain torque to restrain movement of the rotatable member from one angular position with respect to the first member. Preferably the magnetic means comprises at least one pair of magnetically co-operable components. Preferably one component of the at least one pair of components is a permanent magnet. In another angular positions without registration of the first and second members free rotation is possible unless and until re-registration occurs.